



SPECIAL FEATURES

- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified
- ❖ Fully Modular Cabling Design
- ❖ Compact Size (140 mm)
- ❖ 120 mm Fluid Dynamic Bearing (FDB) Fan
- ❖ Seasonic Hybrid Silent Fan Control
- ❖ Highly Reliable Japanese 105 °C Aluminum Electrolytic Capacitors
- ❖ Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3%]
- ❖ Cable-free Connection Design
- ❖ Multi-GPU Technology Support

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
SSR-850PX	20 A	20 A	70 A	0.3 A	3 A	850 W
		100 W	840 W	3.6 W	15 W	
SSR-750PX	20 A	20 A	62 A	0.3 A	3 A	750 W
		100 W	744 W	3.6 W	15 W	
SSR-650PX	20 A	20 A	54 A	0.3 A	3 A	650 W
		100 W	648 W	3.6 W	15 W	
SSR-550PX	20 A	20 A	45 A	0.3 A	3 A	550 W
		100 W	540 W	3.6 W	15 W	



CONNECTOR QUANTITY

Model	Number of Total Connectors					
	Main Power (20+4 Pin) 610 mm	EPS 12 V / ATX 12 V (4+4 Pin) 650 mm	PCI-E (6+2 Pin)	SATA	Peripheral (4P)	FDD (4P)
SSR-850PX	1	2	6 (3 cables)	10	5	1
SSR-750PX	1	2	4 (2 cables)	8	3	1
SSR-650PX	1	1	4 (2 cables)	8	3	1
SSR-550PX	1	1	2 (1 cable)	6	3	1



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com